



Housing

Design and specifications are subject to change without notice. 127

PIH 500(L)/5001N/5005M/5004(L,LBK)/WM/26WM



Specifications


Bracket					
Model No.	Adjustment	Maximum Load	Construction	Dimension(mm)	Weight
Camera Bracket					
PIH-500	Pan: 360° Tilt: +90°	2kg	ABS Injection	76 (W) x 153 (H) x 73 (D)	80g
PIH-500L	Pan: 360° Tilt: +90°	2kg	ABS Injection	76 (W) x 218 (H) x 73 (D)	100g
PIH-5001N	Pan: 360° Tilt: +90°	2kg	Aluminum	123 (L) x 45 (Φ)	110g
PIH-5005M	Pan: 360° Tilt: +90°	5kg	Aluminum	164 (L) x 119 (Φ)	280g
PIH-5004	Pan & Tilt	10kg	Aluminum, Light Gray Textured	85 (W) x 309 (H) x 99 (D)	600g
PIH-5004L	Pan & Tilt	10kg	Aluminum, Light Gray Textured	61 (W) x 240 (H) x 83 (D)	300g
PIH-5004LBK	Pan & Tilt	10kg	Aluminum, Black Textured	61 (W) x 240 (H) x 83 (D)	300g
PIH-WM	-	5kg	Aluminum, Creamy White Textured	132 (W) x 111 (H) x 169 (D)	600g
PIH-26WM	-	2kg	ABS Injection	120 (W) x 65 (H) x 144 (D)	95g

PIH 5003/303PEX/301BH



Specifications

Bracket					
Model No.	Adjustment	Maximum Load	Construction	Dimension(mm)	Weight
Scanner Bracket					
PIH-5003	Pan	10kg	Aluminum, Light Gray Textured	85 (W) x 309 (H) x 99 (D)	450g
Extension Tube					
PIH-303PEX	-	-	Aluminum, Light Gray Textured	300(H)	-
Pilot Head					
PIH-301BH	-	1.5kg	Aluminum, Silver Gray Baked Enamel Finish	177(W) x 109 (H) x 106 (D)	800g



BRACKET **LILIN**®


PIH 303B/303P/303BX/510CPM




PIH-303B



PIH-303P



PIH-303BX



PIH-510CPM

Specifications

Bracket					
Model No.	Maximum Load	Construction	Dimension(mm)	Weight	Strap
PIH-7625 Bracket					
PIH-303B (Wall Mount)	3kg	Aluminum, Light Gray Textured	148 (W) x 385 (H) x 175 (D)	1.2kg	-
PIH-303P (Pendant Mount)	3kg	Aluminum, Light Gray Textured	148 (W) x 335 (H) x 175 (D)	1.1kg	-
PIH-303BX	30kg	Steel, Light Gray Texture	180 (W) x 318.5(H) x 214 (D)	3.9kg	-
PIH-510CPM (Corner & Pole Mount)	25kg	Aluminum, Light Gray Textured	275 (W) x 91(H) x 182 (D)	0.5kg	Stainless Strap for Pole x2 Diameter Range 2.5~7 inch

CAMERA

FAST DOME & ACCESSORY

DVR & ACCESSORY

IP PRODUCT

HOUSING & BRACKET

SCANNER & CONTROLLER

MATRIX & KEYBOARD

MONITOR


Design and specifications are subject to change without notice. 133

PIH 520(L, LB, G, HB)/CPM/510CPM/303(B, P)/76WM



Specifications

Bracket					
Model No.	Maximum Load	Construction	Dimension(mm)	Weight	Strap
PIH-75 Series / ST025 / ST030 / ST035 / IPS025 / IPS030 / IPS035 Bracket					
PIH-520L (Wall Mount)	-	Aluminum	100 (W) x 160 (H) x 210 (D)	0.78Kg	-
PIH-520LB (Wall Mount)	-	Aluminum	204 (W) x 284 (H) x 255 (D)	3.1Kg	-
PIH-520G (Swan Neck)	-	Steel	455 (W) x 755 (H) x 83 (D)	6.8Kg	-
PIH-520HB (Pendant Mount)	-	Aluminum	204 (W) x 284 (H) x 149.5 (D)	2.7Kg	-
PIH-CPM (Corner & Pole Mount)	20kg	Aluminum	156.6 (W) x 126 (H) x 86.8 (D)	0.44Kg	Stainless Strap for Pole x2
PIH-510CPM (Corner & Pole Mount)	25kg	Aluminum, Light Gray Textured	275 (W) x 91(H) x 182 (D)	0.5kg	Stainless Strap for Pole x2 Diameter Range 2.5~7 inch
PIH-76 Series / ST125 / ST130 / ST135 / IPS125 / IPS130 / IPS135 Bracket					
PIH-303B (Wall Mount)	3kg	Aluminum, Light Gray Textured	148 (W) x 385 (H) x 175 (D)	1.2kg	-
PIH-303P (Pendant Mount)	3kg	Aluminum, Light Gray Textured	148 (W) x 335 (H) x 175 (D)	1.1kg	-
PIH-76WM (Wall Mount)	5Kg	Aluminum	150(W) x 110 (H) x 171 (D)	0.5Kg	-



PRH-5440/5840

PRH-5218

INFRARED ILLUMINATOR

**PRH 5218/5440/5840**

Specifications

⊕ Infrared Illuminator				
Model No.		PRH-5218	PRH-5440	PRH-5840
Power Input Voltage		DC12V ±10%	AC24V ±10%	AC90 ~ 260V max.
Radiant Distance		18m (59ft)	40m (131ft)	
Window		Φ 59	Φ 88	
Infrared LED	Wave Length	850nm		
	Angle	30°	20°	
	Quantity	21 units	12 units	
	Power On	Sensor Auto Control		
IP Rating		IP68	IP66	
Mounting		Bottom		
Construction		Aluminum		
Power Consumption		2.0W	7.2W	
Operating Temperature		-20°C ~ + 60°C (-4°F ~ + 140°F)		
Dimension		Φ 65 x 65.1mm	Φ 100 x 185mm	
Weight		160g	1060g	

CAMERA

FAST DOME & ACCESSORY

DVR & ACCESSORY

IP PRODUCT

HOUSING & BRACKET

SCANNER & CONTROLLER

MATRIX & KEYBOARD

MONITOR

Design and specifications are subject to change without notice. 135