



Housing

Design and specifications are subject to change without notice. 127

PIH 5040S



Specifications

Indoor Housing

Model No.	PIH-5040S
Mounting	Bottom
Construction	Aluminum
Window Dimension (mm) / Glass Thickness	74(W) x 64 (H) / 5mm
Dimension (mm)	140(W) x 115(H) x 373 (D)
Weight	1.3kg

PIH 5030 Series/5040/5063/5084



PIH-5030 Series



PIH-5040



PIH-5063




PIH-5084

Specifications

Outdoor Housing

Model No.	PIH-5030 Series	PIH-5040	PIH-5063	PIH-5084
Mounting	Bottom	Bottom	Bottom	Bottom
Construction	Aluminum	Aluminum	Aluminum	Aluminum
Window Dimension (mm) / Glass Thickness	84(W) x 60 (H) / 5mm	84(W) x 60 (H) / 5mm	Φ 110 Heat Resistant Glass / 5mm	Φ 78 Heat Resistant Glass / 3mm
Dimension (mm)	142(W) x 104(H) x 386 (D)	142(W) x 104(H) x 386 (D)	Housing: Φ 134 x 318mm (L) Bracket: 211.5mm (L)	Housing: Φ 112 x 384mm (L) Bracket: 211.5mm (L)
Weight	2.5kg	2.0kg	2.0kg	1.9kg
Ext. Model	PIH-5030H (Heater) PIH-5030B (Blower) PIH-5030HB (Heater & Blower)	-	PIH-5063: AC230V (Heater & Blower) PIH-5064: AC24V (Heater & Blower) PIH-5067: AC117V (Heater & Blower)	PIH-5084: AC24V (Heater) PIH-5088: AC90~260V (Heater)



HOUSING **LILIN**

PIH 510 (for PTZ PIH 7625 only)



PIH-510G/510GIP



PIH-510H/510HIP



PIH-510L/510LIP

Specifications

Outdoor Dome Housing

Model No.	PIH-510G / PIH-510GIP		PIH-510H / PIH-510HIP	PIH-510L / PIH-510LIP
Type	Swan Neck		Pendant Mount	Wall Mount
Heater Activation	On: < 15°C Off: > 25°C			
Fan Activation	On: > 35°C Off: < 25°C			
Operating Temp.	-30°C ~ + 50°C (-22°F ~ + 122°F)			
Input Voltage	DC 12V			
Construction	Bracket	Aluminum		
	Top	Flame Resistant ABS		
	Internal Fixing	Steel		
	Housing	Polycarbonate		
Dimension (mm)	Total Height	875	477.5	367.15
	Total Width	685	274	405
	Dome (Φ)	270	270	270
	Base (Φ)	180	-	-
Weight	10kg		4.8kg	5kg

CAMERA

FAST DOME & ACCESSORY

DVR & ACCESSORY

IP PRODUCT


HOUSING & BRACKET

SCANNER & CONTROLLER

MATRIX & KEYBOARD

MONITOR

Design and specifications are subject to change without notice. 129



LILIN HOUSING

PIH 5480/5880/5480M/5880M/54200/58200


PIH-54200/58200

PIH-5480/5880
PIH-5480M/5880M

Specifications

⊕ Infrared Illuminator Housing

Model No.		PRH-5480	PRH-5880	PRH-5480M	PRH-5880M	PRH-54200	PRH-58200
Power Input Voltage		AC24V ±10%	AC90 ~ 260V max.	AC24V ±10%	AC90 ~ 260V max.	AC24V ±10%	AC90 ~ 260V max.
Radiant Distance		100m		60m		200m	
Window		Φ 110 Heat Resistant Glass					
Glass Thickness		3mm					
Infrared LED	Wave Length	850nm					
	Angle	10° + 30°		30°		6° + 30°	
	Quantity	11 units (10°) + 6 units (30°)		17 units		5 units (6°) + 2 units (30°)	
	Power On	Sensor Auto Control, Adjustable Control Point				Sensor Auto Control, Adjustable Control Point	
Blower Control		On: 35℃ Off: 25℃					
Heater Control		On: 15℃ Off: 25℃					
Suitable Camera and Lens		Max. 200mm length					
IP Rating		IP66					
Mounting		Bottom					
Construction		Aluminum					
Power Consumption		22W				32W	
Operating Temperature		-20℃ ~ + 60℃ (-4°F ~ + 140°F)					
Dimension		Housing : Φ 134 x 318mm (L), Bracket : 205mm (L)			Housi ng : Φ 134 x 318mm (L), Bracket : 211.5mm (L)		
Weight		3500g					



HOUSING **LILIN**



PIH 9480/9880



Specifications

⊕ Invisible Infrared Illuminator Housing

Model No.		PRH-9480	PRH-9880
Power Input Voltage		AC24V ± 10%	AC90 ~ 260V max.
Radiant Distance		80m	
Window		Φ 110 Heat Resistant Glass	
Glass Thickness		3mm	
Infrared LED	Wave Length	940nm	
	Angle	6° + 30°	
	Quantity	5 units (6°) + 2 units (30°)	
	Power On	Sensor Auto Control, Adjustable Control Point	
Blower Control		On: 35℃ Off: 25℃	
Heater Control		On: 15℃ Off: 25℃	
Suitable Camera and Lens		Max. 200mm length	
IP Rating		IP66	
Mounting		Bottom	
Construction		Aluminum	
Power Consumption		32W	
Operating Temperature		-20℃ ~ + 60℃ (-4°F ~ + 140°F)	
Dimension		Housing : Φ 134 x 318mm (L), Bracket : 211.5mm (L)	
Weight		3500g	

CAMERA

FAST DOME & ACCESSORY

DVR & ACCESSORY

IP PRODUCT

HOUSING & BRACKET

SCANNER & CONTROLLER

MATRIX & KEYBOARD

MONITOR

Design and specifications are subject to change without notice. 