


Monitor

Design and specifications are subject to change without notice. 147



LILIN MONITOR

PMH L17AC/L19AC



Specifications

LCD Monitor

Model No.		PMH-L17AC	PMH-L19AC
LCD Panel	Display Area	17.0" Viewable	19.0" Viewable
	Brightness	300cd / m2	
	Contrast Ratio	1000 : 1	
	Response Time	5 ms	
	Viewing Angle	165° Horizontal , 165° Vertical	
Max. Resolution		1280*1024 @75Hz	
PC Signal	Analog	RGB Analog	
	Frequency	FH: 31 ~ 82 KHz , FV: 50 ~ 75 Hz	
CVBS signal	CVBS & S-Video	CVBS / FH : 15.75KHz , FV : 60Hz	
		3D Comb Filter & 3D De-Interlace	
Screen Protection		Auto Image Move	
OSD Language	Analog RGB	15-pin Mini D-sub	
	CVBS	BNC	
	S-Video	Mini-Din	
	PC Audio	Phone Jack (Stereo)	
	CVBS Audio	RCA Jack (L/R)	
	Power	DC Jack (12V)	
Output Connector	CVBS	BNC	
Speaker		2 x 2W	
Power	Adapter	AC 100 ~ 240V , 50 / 60Hz , 12V / 4.16A	
	Consumption	VESA-DPMSiF50W (Max.)	
OSD Language		Multi-Language	
Operating Conditions	Temperature	32°F to 104°F (0°C to 40°C)	
	Humidity	30 ~ 80% (Non-Condensing)	
Safety & EMI		CE, FCC	