Scanner

利凌年度型錄.indd 137 2009/4/15 下午 01:53:01

LILIN CONTROLLER

PIH 301C/302C/306/307/308

Specifications

Outdoor Pan / Tilt Control

Model No.	PIH-301C	PIH-302C
Input Voltage	117 / 230Vac	
Output Voltage	24 / 117 / 230Vac	
Control Buttons	AUTO / OFF / MANUAL, LEFT / RIGHT / UP / DOWN	
Construction	Steel,Silver Gray Baked Enamel Finish	

Specifications

Scanner Control

Model No.	PIH-306
Input Voltage	117 / 230Vac
Output Voltage	24 / 117 / 230Vac
Control Buttons	AUTO / OFF / MANUAL, LEFT / RIGHT
Construction	Steel,Silver Gray Baked Enamel Finish

Specifications

Scanner Control 5-Channel

Model No.	PIH-307
Input Voltage	117 / 230Vac
Output Voltage	24 / 117 / 230Vac
Control Buttons	AUTO / OFF / MANUAL, LEFT / RIGHT
Construction	Steel,Silver Gray Baked Enamel Finish

Specifications

Multiple Pan/Tilt/Lens Control

Model No.	PIH-308
Input Voltage	24 / 117 / 230Vac
Pan/Tilt Output voltage	24 / 117 / 230Vac
Lens Output Voltage	8~16Vac(adjustable)
Lens Control	Zoom, Focus, Iris
Number of PTZ	5 x PTZ

利凌年度型錄.indd 138 2009/4/15 下午 01:53:11

SCANNER

PIH 302

Specifications

Indoor Pan/Tilt	
Model	PIH-302
Input voltage	24 / 117 / 230Vac
Pan Speed	6° / sec
Pan Travel	355° ,Adjustable limit stops
Tilt Speed	4° / sec
Tilt Travel	+30° UP,-40° Down
Maximum Load	Pan 7Kg Tilt 4Kg
Duty Cycle	Pan: continuous Tilt: intermittent
Seals	Dust-proof Gasket seals

PIH 305/305S

PIH-305S



PIH-305

Specifications

Indoor Scanner		
Model	PIH-305	PIH-305S
Input voltage	24 / 117 / 230Vac	
Pan Speed	6° / sec	
Pan Travel	350° ,Adjustable limit stops	
Tilt Adjustment	90° Down	
Maximum Load	7Kg	
Duty Cycle	continuous	
Seals	Dust-proof Gasket seals	

利凌年度型錄.indd 139 2009/4/15 下午 01:53:16

LILIN SCANNER

PIH 303

Specifications

Outdoor Pan/Tilt	
Model No.	PIH-303
Input Voltage	24 / 117 / 230Vac
Pan Speed	6° / sec
Pan Travel	355°, Adjustable limit stops
Tilt Speed	3° / sec
Tilt Travel	+50° UP,-50° Down
Maximum Load	15 Kg
Duty Cycle	Pan : continuous Tilt: intermittent
Seals	Water-proof Gasket seals

利凌年度型錄.indd 140 2009/4/15 下午 01:53:21

CONTROLLER

PIH 6001/6002 & PS 10

Specifications

Video Amplifier

Model No.	PIH-6001
System	NTSC / PAL
Input Voltage	117 / 250Vac
Gain / HF Frequency	10Hz ~ 4.5MHz (±3dB)
Video Output	0.4 ~ 2.0Vp-p 75Ω
Video Input	CVBS 1.0Vp-p 75Ω
Maximum Video Gain	12dB (±3dB)
Frequency Bandwidth	4.5MHz

Specifications

Video Distributor

Model No.	PIH-6002
System	NTSC / PAL
Input Voltage	117 / 250Vac
Gain / HF Frequency	10Hz ~ 15MHz
Video Output	4 x 1.0 ~ 2.0Vp-p 75Ω
Video Input	1 x 1.0 ~ 2.0Vp-p 75Ω
Maximum Video Gain	1dB
Frequency Bandwidth	1Hz ~ 15MHz

Specifications

Power Supply

Model No.	PS-10
Input Voltage	117 / 230Vac
Current	5A
Output Voltage	24Vac

利凌年度型錄.indd 141 2009/4/15 下午 01:53:25

利凌年度型錄.indd 142 2009/4/15 下午 01:53:30